

DeSoto[®] CN59 Surface Degreasing Cleaner

TECHNICAL DATA SHEET

Product Description

DeSoto[®] CN59 is based on a water and organic solvent blend that is suitable for the cleaning of metallic and non-metallic surfaces prior to painting. CN59 is effective in removing fingerprints, oils, grease and general dirt from cured painted surfaces. CN59 can also be used to clean plastics, rubber, sealants, composites, glass and bare metals.

- Multi purpose cleaner
- Compliant with European solvent emissions directive (SED)
- Compliant with UK process guidance note PG6/45
- Can be used to remove uncured paint overspray

Components

Mix Ratio (by volume)

- N/A - Supplied ready for use

Specifications



CN59 meets the requirements of:

- Def Stan 80-222


Note: PPG Aerospace recommends you check the most recent specification QPLs for updated information.

Instructions for Use



It is recommended to use clean lint free, absorbent industrial cloths or paper wipes in conjunction with CN59. Pour the CN59 onto the wipes to avoid contamination of the cleaner.

Note: All products and components should be placed in ambient conditions of 15-30°C (59-86°F) for at least 24 hours prior to mixing and application.



Pot Life:

N/A



DeSoto® CN59 Surface Degreasing Cleaner

Application Guidelines

Application:

A wipe on / wipe off technique is recommended. Frequently replace soiled wipes to ensure the surface is clean and smear free. Once dry, the surface is ready for painting.



NOTE:

Contaminated wipes should be treated as flammable waste.

Physical Properties



Appearance:

Colourless liquid



VOC: (ASTM)

CN59 285 g/Lt



Flash Point:

CN59 30°C (86°F)

Shelf Life:

CN59 24 months in original unopened container

Note: Shelf life may vary due to OEM specification requirements. Refer to container label for specific shelf life information.

Note: The application and performance property values above are typical for the material, but not intended for use in specifications or for acceptance inspection criteria because of variations in testing methods, conditions and configurations.

Storage Recommendations



Inspect the condition of the container to ensure compliance. The material should be stored at temperatures between 5°C to 35°C (41°F to 95°F) to ensure shelf life.

Note: When procuring to a qualified material specification, follow those storage instructions.



DeSoto[®] CN59 Surface Degreasing Cleaner

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An SDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

Additional information can be found at: www.ppgaerospace.com

For sales and ordering information call the local PPG office at the numbers listed below:

Asia Pacific

ASC – Australia

Tel 61 (3) 9335 1557
Fax 61 (3) 9335 3490

ASC – Japan

Tel 81 561 35 5200
Fax 81 561 35 5201

ASC – South East Asia

Tel 65 6861 1119
Fax 65 6861 6162

ASC – Suzhou

Tel (86-512) 6661 5858
Fax (86-512) 6661 6868

ASC – Tianjin

Tel (86-022) 2482 8625
Fax (86-022) 2482 8600

Europe and Middle East

ASC – Central Europe

Tel 49 (40) 742 193 10
Fax 49 (40) 742 139 69

ASC – Middle East & India

Tel (971) 4 883 9666
Fax (971) 4 883 9665

ASC – North Europe

Tel 44 (0) 1388 770222
Fax 44 (0) 1388 770288

ASC - South Europe

Tel 33 (0) 235 53 43 71
Fax 33 (0) 235 53 54 44

Americas

1 (818) 362-6711 or 1-800-AEROMIX

DeSoto is trademark of PRC-DeSoto International, Inc.

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

PPG Aerospace
Sealants and Coatings
Darlington Road
Shildon, Co Durham UK
DL4 2QP

www.ppgaerospace.com

Issue Date: 07/17
Lit: 4326